

# LAMINAR FLOW INTERLOCKING PASS THRU



## STANDARD FEATURES

- Solid 18 ga. 304 stainless steel construction with #4 brushed finish.
- Mechanical interlocking door system.
- Coved interior corners.
- 3/8" thick acrylic safety glass doors.
- Continuous compression bulb gasket.
- HEPA filtration 99.99% EFF @ .3 microns.

## OPTIONAL FEATURES

- Tinted acrylic glass (doors).
- 1/4" safety or tempered glass (doors).
- Low wall air return system.
- 316L stainless steel construction.
- Cycle timed activation.
- Finish trim kit.
- Support gussets for cantilever mounting.
- ULPA filtration 99.9995% EFF @ .12 microns.

## NOTE:

- **Isolation Systems, Inc.** inspection reports available upon request.
- Optional trim kits are recommended for all installations.
- All filters are PSL challenged at factory. Certificates of conformance are available upon request.
- All electrical components are UL listed.
- All electrical wiring is in conformance w/NEMA standards .
- Approval drawings available upon request.

*\*be sure to include kit part # when ordering optional trim or gusset kit*

MODEL #	O.A. UNIT SIZE	INSIDE DIM	ELECTRICAL	TRIM KIT*	GUSSET KIT*	SHIP WT
PTLF-22	39 1/2"h x 29 1/4"w x 24"d	24 " x 24" x 24"	115v-60 hz -1 ph	TK-04	SG-14	195 lb

*All information herein is subject to change without notice  
All shipping weights estimated.*

*All catalog dimensions are nominal*

