

COVERED CORNER INTERLOCKING PASS THRU



STANDARD FEATURES

- Solid 18 ga. 304 stainless steel construction with #4 finish.
- Mechanical interlocking door system.
- Coved interior corners.
- 3/8" thick acrylic safety glass doors.
- Continuous compression bulb gasket.

NOTE:

- **Isolation Systems, Inc.** inspection reports available upon request.
- Optional trim kits are recommended for all installations.

OPTIONAL FEATURES

- 316L stainless steel construction.
- Polyurethane-coated 18 ga. CRS construction with stainless steel floor.
- Stainless steel framed laminated safety glass doors.
- Tinted acrylic glass (doors).
- 1/4" safety or tempered glass (doors).
- UV lighting.
- N² purge system.
- Custom sizes.
- Finish trim kit.
- Support gussets for cantilever mounting.
- Silicone gasket.

**be sure to include kit part # when ordering optional trim or gusset kit*

MODEL #	O.A. UNIT SIZE	INSIDE DIM	TRIM KIT#*	GUSSET KIT#*	SHIP WT
PT-12	19½"h x 23¼"w x 18"d	18" x 18" x 18"	TK-01*	SG-14*	115 lb
PT-22	25½"h x 29¼"w x 24"d	24" x 24" x 24"	TK-02*	SG-14*	140 lb
PT-33	31½"h x 35¼"w x 24"d	30" x 30" x 24"	TK-03*	SG-14*	165 lb

*All information herein is subject to change without notice
All shipping weights estimated.*

All catalog dimensions are nominal.

